


752 PLASTIC HAND TOOL

- 4" wide all plastic body
- single jet / open spray
- plastic valve and lever
- for light duty jobs



752

70500 METAL UPHOLSTERY TOOL

- 4" wide pick-up head with 9" handle
- stainless steel construction
- brass valve
- valve designed for up to 300 P.S.I.
- open spray design



70500 metal upholstery tool

70600 STANDARD DETAILING TOOL

- 3.5" wide pick-up head
- all stainless steel construction with aluminum valve
- reach into crevices and small places - ideal for upholstery or car detailing companies
- valve designed for up to 400 P.S.I.
- external spray design



70600 standard detailing tool

70700 ECONOMY DETAILING TOOL

- 3.5" wide impact resistant plastic see-thru head
- allows clear view of recovery
- stainless steel tube handle
- easy to remove jet for quick cleaning
- external spray
- valve designed for up to 400 P.S.I.



70700 economy detailing tool

70800 METAL CREVICE TOOL

- internal spay complete with air bleeder valve
- stainless steel construction
- ideal for car detailing companies
- valve designed for up to 400 P.S.I.

70800 crevice tool



80100 SINGLE JET EXTRACTION WAND

- 12" wide all stainless steel head with single bend wand
- single jet
- overspray control wings
- stiffened ribs to prevent glides from collapsing
- vinyl sleeve to protect hands from heat
- assist handle included

80250 DELUXE 2 JET EXTRACTION WAND

- 12" wide all stainless steel head with double bend wand
- dual jets; no manifold
- overspray control wings
- stiffened ribs to prevent glides from collapsing
- vinyl sleeve grip to protect hands from heat
- assist handle included
- dipped valve lever



80100 / 80250 / 596

596 EXTRACTION WAND

- 10" wide single bend steel wand with plastic head
- dual jet manifold
- plastic valve and lever
- for light duty jobs

80050 ECONOMY 1 JET EXTRACTION WAND (not shown)

- 12" wide all stainless steel head with single bend wand
- single jet
- stiffened ribs prevent glides from collapsing

All tools and wands are stocked items in "B" style quick-disconnects. If required, "A" style quick-disconnects (small) must be specially requested when placing your order.