

The most efficient floor machine system ever.

Our floor polishers are designed to meet your high floor maintenance requirements while offering quality, dependability, safety and durability.



**Rotationally-moulded brush shroud**  
will not rust or dent

**Removable handle**  
for easy transport

**Module electrical components**  
allow for easy servicing

**Trigger safety lock**  
allows operator fingertip control while preventing machine from being accidentally turned on

**Quick lock mechanism**  
for easy handle adjustment, allowing operator to adjust handle without bending

**Additional Dual Speed Features :**

- Motor brush wear indicator
- Complete with drive disc

**\*19 inch Dual Speed is now available with LA (long arm) fixed handle upon special request (extended delivery times may be required)**

| SPECIFICATIONS  | SINGLE SPEED        | DUAL SPEED                     |
|-----------------|---------------------|--------------------------------|
| MOTOR           | AC Dual Capacitor   | Permanent magnet               |
| HP              | 1.5 hp              | 1.5 hp                         |
| VOLT            | 115 AC              | 115 AC                         |
| AMP             | 14                  | Low 10 -High 13                |
| MOTOR RPM       | 1740 rpm            | 3200 rpm                       |
| NOISE LEVEL     | 55 db (A)           | Low 60 db (A) - High 63 db (A) |
| GEARBOX TYPE    | 3 idler -10:1 ratio | 3 idler - ratio 10:1           |
| CABLE           | 14/3 - 50' (15m)    | 14/3 - 50' (15m)               |
| NET WEIGHT      | 87 lbs - 39.5 kg    | 87 lbs - 39.5 kg               |
| SHIPPING WEIGHT | 100 lbs - 45.5 kg   | 100 lbs - 45.5 kg              |
| SIZE            | 17" or 19"          | 17" or 19"                     |
| DRIVE BLOCK     | not included        | included                       |

**Optional Accessory**

**19201**  
Water Tank for Round Handled Machine



**User-friendly innovative design.**

Offers removable handle for easier transportation and quick handle adjustment for operator.

Variable pad pressure can be adjusted easily to maximize performance.

Both models are lightweight and maneuverable with non-marking caster and wheels.

Rotationally-moulded brush shroud will not rust or dent.



| SPECIFICATIONS        | DUAL SPEED BURNISHER           | UHS BURNISHER                 |
|-----------------------|--------------------------------|-------------------------------|
| MOTOR                 | Permanent magnet               | Permanent magnet              |
| HP                    | 1.5 hp                         | 1.5 hp                        |
| VOLT                  | 115 AC                         | 115 AC                        |
| AMP                   | Low 10 amps-High 13 amps       | 13                            |
| MOTOR RPM             | 1500 rpm                       | 2000 rpm                      |
| NOISE LEVEL           | Low 58 db (A) - High 61 db (A) | 61 db (A)                     |
| GEARBOX TYPE          | Direct drive                   | Direct drive                  |
| CABLE                 | 14/3 - 75' (22.55m)            | 14/3 - 75' (22.55m)           |
| NET WEIGHT            | 70 lbs - 32 kg                 | 70 lbs - 32 kg                |
| SHIPPING WEIGHT       | 88 lbs - 40 kg                 | 88 lbs - 40 kg                |
| SIZE                  | 20" (uses 19 inch floor pads)  | 19" (uses 19 inch floor pads) |
| DRIVE BLOCK           | included                       | included                      |
| CENTRE-LOK PAD HOLDER | included                       | included                      |
| DUST COLLECTION KIT   | Optional                       | included                      |