

**Quality Cleaning Equipment Designed For Versatility  
Offering Solutions To Your Carpet Cleaning Problems.**

**Standard Features on PR100 and PR375**

- Waist-high switches & hose connections
- 11 gallon solution tank
- Durable 5" casters with 12" rear wheels
- Extension cord connection with 50' power cord
- Easy access motor compartment for maintenance
- Toilet-high drain valve for convenient drainage
- 12 gallon recovery tank
- Built in pull handle/cord wrap
- Twist-on recovery tank lid



**PR100**

Standard with a 100 p.s.i. demand pump and dual vacuum motors. Extractor comes complete with 25 foot vacuum and solution hose. The PR100 is the ideal machine for regular maintenance cleaning.

**PR375**

Standard with a 375 p.s.i. CAT pump and dual vacuum motors. Variable pressure regulator (optional). Extractor comes complete with 25 foot high pressure vacuum and solution hose. The PR375 is the professional's choice.

**PR50**

Provides excellent performance in a user friendly, easy-to-transport compact package. The PR50 has a 60 p.s.i. demand pump and a single 2-stage vacuum motor. Standard features include removeable recovery tank for easy emptying, fold down handles for convenient storage and transportation.

Ideal for homes, hospitals, nursing homes, hotels, motels and also great for a rental unit.



**PR700**



**PREMIER 700  
SELF CONTAINED  
EXTRACTOR**

The PREMIER 700 has been designed for all-in-one extraction cleaning convenience. Features include a lift-off recovery bucket, 26.5L (7 US GAL) capacity tank, self-levelling power brush, 50 PSI pump, three-stage by-pass vacuum motor and four (7") non-marking wheels for maneuverability and stability. Cleaning head is offset to allow cleaning close to walls and corners. Roto-cast polyethylene body is mounted on a tubular steel frame to provide a tough but very manageable self-contained unit. Entela approved.



## Carpet Extractors

PREMIER SPECIFICATIONS				
Model	PR50	PR100	PR375	PR700
Vacuum Motors	1 x 2 stage	2 x 2 stage	2 x 2 stage	1 x 3 stage
115AC	1.25 HP	2 x 1.25 HP - 2 stage tangential by-pass ball/ball		1.5 HP High performance
Vacuum Motor Amps(each)	7.9	7.9	7.9	12
C.F.M.* (per motor)	93	93	93	112
Waterlift*	82"	150"	150	117"
Pumps	60 PSI demand	100 PSI demand	375 PSI CAT pump	50 PSI demand
Pumps/Amps	0.7	1.0	1.0	1.0
Solution Tank Capacity in U.S. gallons	3 gal. (11.4 L)	11 gal. (42 L)	11 gal. (42 L)	7 gal. (26.5 L)
Recovery Tank Capacity in U.S. gallons	2 gal. (7.5L)	12 gal. (45 L)	12 gal. (45 L)	7 gal. (26.5 L)
Cord Set	25' (7.5 m) (16/3 yellow)	50' (15m) (12/3 yellow)	50' (15m) (12/3 yellow)	40' (14/3 SJTW)
Casters	2 X 2"	2 X 5"	2 X 5"	Not Applicable
Wheels	2 X 6"	2 X 12"	2 X 12"	4 X 7"
Hose Assembly	Optional	25' included	25' high pressure incl.	Optional
Drain Valve	Not Available	Yes	Yes	Not Available
Lift off recovery bucket	Yes	No	No	Yes
Tank Construction	High Density Roto Molded Polyethylene			
Operating Total Amp	8.5	12.5	13.3	14.0
Height	38" (97 cm)	40" (102 cm)	40" (102 cm)	30"
Weight (net)	41 lbs. (18.6 kg)	74 lbs. (33.6 kg)	95 lbs. (43.1 kg)	78 lbs. (35.4 kg)
Weight (shipping)	47 lbs. (21.3 kg)	80 lbs. (36.3 kg)	100 lbs. (45.4 kg)	90 lbs. (40.9 kg)

*Bringing you solutions for your cleaning problems*



Distributed By: 