



Professional Line Wet /Dry Vacuums

M80 features:

This dry use vacuum is the quietest operator in the family. Offers light-weight mobility, ideal for areas where floor space is limited. Tool kit extra. Uses tool kit #MTK1



M50 features:

Dry use vacuum ideal for lobbies, hallways, conference rooms, institutional, commercial and industrial buildings. Hard working, quiet and mobile. Tool kit extra. Uses tool kit # MTK2



M60 features:

High performance wet and dry pickup with a five-wheel, non-tipping, non-corrosive tank gives years of dependable service. Wet filter included. Tool kit extra. Uses tool kit #MTK3

**Optional Hepa-type filters are available upon request
Two year limited warranty on parts and labour.**

Our top-of-the-line family of vacuum cleaners offers versatility and durability for today's health conscious environment.

Model	M50 (dry only)	M60 (wet/dry)	M80 (dry only)
Rated Horsepower	1.4	1.6	1.4
Motor Type (ball/ball)	2-stage flow-thru	2-stage bypass	2-stage flow thru
Rated Amps	9.0	10.2	9.0
Rated Volts	115 AC	115 AC	115 AC
Total Capacity	25 L 5.5 Imp. Gal 6.6 US Gal	25 L 5.5 Imp. Gal 6.6 US Gal	20L 4.4 Imp. Gal 5.2 US Gal
Recoverable Capacity	21 L 4.6 Imp. Gal 5.5 US gal	21 L 4.6 Imp. Gal 5.5 US gal	14 L 3.0 Imp. Gal 4.0 US gal
Waterlift (at closed orifice)	90.2"	91.5"	90.2"
C.F.M. (at tank orifice)	94	103	94
Motor RPM at full load	23,200	23,400	23,200
Noise Level (1.5 m)	59 dB	62 dB	59 dB
Jogger - Filter Surface Area	372 sq.in.	372 sq.in.	284 sq.in.
Hose Size	1 1/2" X 8'	1 1/2" X 8'	1 1/2" X 8' 1 1/4" end cuff
Cable Length	50'	50'	35'
Casters / Wheels	5 X 2"	5 X 2"	4 X 2"
Height	22"	22"	19"
Net Weight	20 lbs.	20 lbs.	18 lbs.
Shipping Weight	29 lbs.	30 lbs.	26 lbs.



Distributed By:



Professional Line Wet /Dry Vacuums

M6018



Both M6012 and M6018 offer high performance wet and dry pickup with non-corrosive tank giving years of dependable service. The M6018 and MTV2-20P models are mounted on a dolly with large 10" rear wheels and 3" swivel casters.

Tool kit extra. Uses tool kit # MTK3

M6018TNP is available with tipping tank and drain plug. Drain hose not included, order PN #M-6018TNP

Tool kit extra. Uses tool kit # MTK3



M6012



MTV2-20P



Two year limited warranty on parts and labour.

Model	M6012	M6018	MTV2-20P
		Both models	
Rated Horsepower	1.6	1.6	2.5
Motor Type (ball/ball)	2 - stage bypass (115volt)		
Rated Amps	10.2	10.2	12.8
Waterlift (at closed orifice)	91.5"	91.5"	113"
C.F.M. (at tank orifice)	103	103	104
Motor RPM. (at full load)	23,400	23,400	16,500
Noise Level (1.5 m)	62 dB	62 dB	78 dB
Jogger - Filter Surface Area	372 sq.in.	372 sq.in.	656 sq.in.
Hose Size	10' X 1 1/2" (3m X 38mm)		
Cable Length	50' SJTW (16/3 Yellow), 15m		
Use	Wet / Dry		
Casters/Wheels	5 X 2"	2 X 3"	2 X 3"
Ball Type		2 X 10"	2 X 10"
Height	27"	37"	37"
Recoverable Capacity	38.3 L	60.6 L	52.2 L
	8.4 Imp.Gal	13.3 Imp.Gal	11.5 Imp.Gal
	10.1 US Gal	16 US Gal	13.75 US Gal
Net Weight	29 lbs.	43 lbs.	50 lbs.
Shipping Weight	31 lbs.	51 lbs.	58 lbs.
Front End Squeegee (Optional)	No	Yes	Yes
Power Nozzle Receptacle	Yes	Yes	No
Drain	Plug	Hose	Plug
Wet Filter	Included	Included	Included

Our Turbo Vac MTV2-20P has a powerful, 2.5 HP electronically balanced, two stage, ball/ball motor. Sturdy, durable and seamless polyethylene tank lasts longer and is easy to maintain. Ideally suited for applications where longer running time, increased suction and a large capacity are required. Best suited for application where longer hose length is required. Tool kit extra. Uses tool kit # MTK3



Distributed By: